

compact DVD player



multiregion



DVD | FullHD | USB

- Dolby-Digital codec
- Chipset MTK1389G
- Lens HD870A
- Audio output: 2.0CH, COAXIAL
- Video output: DV-OUT, CVBS, SCART
- USB
- Multimedia
- Subtitles
- Main menu in languages: Polish, English, Italian, German, French

Akcesories:

- Remote Control Unit
- Manual



Inputs/Outputs



rear panel

1. HDMI
2. Scart
3. 2 x RCA Audio
4. SPDIF/coaxial RCA
5. 1 x RCA Video



front panel

1. 1 x USB

RCU

The Regent D-225 is supplied with an extremely convenient and intuitive remote control with the RCU D-225 symbol. This remote control fits in the hand, that allows you to conveniently operate all the functions of the player.



Technical Specifications

- **Processor:** Mediatek MT1389g
- **Housing:** black, ABS material. A set of AV connectors is on the rear panel, a USB port on the front. The display, buttons, drive tray opening and the infrared sensor are located on the front of the player.
- **Connectors:**
 - HDMI output (up to 1080p 60Hz)
 - Video Composite (CVBS) output
 - Stereo audio output (analog, 2x chinch)
 - Digital audio output (electric)
 - HOST USB 2.0 connector (power >500mA)
- **The format of external drives connected via USB:** FAT16, FAT32; max 2TB capacity; GPT partition tables are not supported.
- **Supported formats and containers:** DVD-Video, VOB, MPEG-1/2 PS (MPG), MPEG-4 Part 14 (MP4), AVI, OGM, DivX 3-6
- **Supported video codecs:** XVID (except 3 warp-point GMC), MPEG-1, MPEG-2, MPEG-4 ASP
- **Maximum supported video resolution:** 720x576
- **Supported audio formats:** MPEG audio (MP1, MP2, MP3), M4A and others
- **Supported audio codecs:** Dolby Digital (AC3) - only SPDIF, MP1, MP2, MP3, Vorbis, DTS - issued on digital outputs (so-called passthrough) and others
- **Supported subtitle formats:** TXT (TMplayer), SRT (SubRip), SMI (Sami), SUB (MicroDVD, SubViewer2), SSA (Sub Station Alpha), ASS (Advanced Sub Station Alpha), MPL (MPL2). All subtitles are supported in their native extensions.
- **Supported code pages:** CP1250, CP1251, CP1252, UTF-8, ISO-8859-1, ISO-8859-2, ISO-8859-5, ISO-8859-15, SUB+IDX (bitmap)
- **Supported photo formats:** JPEG, HD JPEG (Baseline)
- **Player power supply:** AC 100~240V
- **Remote control power supply:** two AAA batteries
- **Dimensions (WxDxH):** 225x200x43mm



5 907115 003696 >

color: black
EAN: 5907115003696
packaging: 16 pcs.

